



Key features at a glance

- Built-in corrosion protection
- Very good adhesion to mineral substrates
- Applicable in large layer thicknesses – practically unlimited layer thickness
- Non-shrinking mortar
- Compressive strength > 20 N/mm² (R2)
- Polymer modified technology
- Creamy mixing and consistency
- Consistency is achieved at the end of the mixing – Continuously decreasing viscosity
- Stable for overhead application
- Long working time (20 – 30 min.)
- Smooth concrete finish
- Stable concrete light grey color – No yellow / brown spotting
- Waterproof
- Good frost-thaw and salt resistance
- Mouldable and Profilable

KÖSTER at your service – worldwide.



// Contact us

KÖSTER BAUCHEMIE AG
 Dieselstraße 1–10 · 26607 Aurich
 Tel.: +49 4941 9709 0
 E-Mail: info@koster.eu
www.koster.eu

Follow us on social media:



Issued: 4/2023

Concrete Repair

with KÖSTER Betomor Multi A



Coarse mortar with a fine concrete smooth finish

Fast and effective concrete repair system

Built-in corrosion protection



KÖSTER Betomor Multi A

In today's modern construction environment, not only green products are required, but intelligent products with high durability.

KÖSTER Betomor Multi A combines three products in one – a built in corrosion protection additive, coarse enough for large layer thicknesses, yet with enough fine aggregates for a smooth finish. This reduces the amount of products that have to be estimated, ordered, delivered, and stored on-site. This shortens and reduces supply chains and makes KÖSTER Betomor Multi A even more environmentally and user friendly.

Add to that the labor involved in applying 3 or more products instead of one, and the only question remaining is "Why not use KÖSTER Betomor Multi A on your next project"?

// Areas of application

For filling and leveling of voids in unlimited layer thicknesses on masonry as well as reinforced and un-reinforced concrete without a separate anticorrosion coating. Also suitable as a fine plaster on mineral substrates (such as, brick, block, concrete, and many types of stone).

// Packaging



15 kg bucket
25 kg bag

Consumption:
Approx. 1.3 kg/l void

// Processing



1 Surface preparation



3 Pre-wetting



5 As soon as the setting begins, the surface can be smoothed with a trowel or float.



2 Mix KÖSTER Betomor Multi A with clean water (4.5 l per 25 kg bag; 2.7 l per 15 kg bucket) to a smooth, lump-free mass.



4 KÖSTER Betomor Multi A is applied with a spatula or a trowel in one step.



6 Finished repair